



Measuring gauge with storage case: includes dial indicator holder, dial indicator, centering piece, and calibrated master.

Function

Using the calibrated master, the distance of the 30 degree clamping slope relative to I 2 is preset using the dial indicator holder. The tool taper to be measured is placed in the centering piece, allowing the variation of the taper to be measured.

HSK A/C/E	HSK B/D/F	I 6 / JS 10	d 6	Order Number
HSK-A 25	HSK 32	7.21	15	410.230.125.000
HSK-A 32	HSK 40	8.92	19	410.230.132.000
HSK-A 40	HSK 50	11.42	23	410.230.140.000
HSK-A 50	HSK 63	14.13	29	410.230.150.000
HSK-A 63	HSK 80	18.13	37	410.230.163.000
HSK-A 80	HSK 100	22.85	46	410.230.180.000
HSK-A 100	HSK 125	28.56	58	410.230.190.000
HSK-A 125	HSK 160	36.27	73	410.230.192.000
HSK-A 160	-	45.98	92	410.230.196.000

TAC Rockford Product Line

Machine Tool Gauges, Tool Changer Alignment, Runout Test Arbors, Workholding Systems, Tool Holders, Adapters and Extensions, Tool Holder Blanks, Machine Tool Accessories, Coolant Tubes and Gauges, Heat Shrink Systems, Rapid Prototyping



109 North Main Street · Rockford, IL 61101 USA
Tel. 815 962-5600 · Fax 815 962-4600
www.TACRockford.com · info@TACRockford.com