

Complete set with case includes measuring ring with dial indicator, measuring gauge for lower deviation, measuring gauge for upper deviation, mean deviation and setting gauge for dial indicator.

Function


The setting gauge is placed into the gauge ring, and the dial indicator is set to zero. The measuring gauge 1 (second gauge pictured) is then used to measure the lower deviation of the drive key, and the measuring gauge 2 (third gauge) for upper deviation.

Taper	Order Number
HSK-A/C 32	410.240.132.000
HSK-A/C 40	410.240.140.000
HSK-A/C 50	410.240.150.000
HSK-A/C 63	410.240.163.000
HSK-A/C 80	410.240.180.000
HSK-A/C 100	410.240.190.000
HSK-A/C 125	410.240.192.000
HSK-A/C 160	410.240.196.000

Preventive Maintenance Gauges

Dimensional Gauges, Balancing Masters, Coolant Supply Gauges, Center Height/Master Setting, Tool Changer Alignment Gauges, Machine Set-up Gauges. Also ask us about custom gauges and personalized solutions for your machine or machine tool.

Runout Test Arbors



Available for all major machine tapers, including CAT/DIN/BT Steep Taper, HSK, Capto, KM, Morse, and others.

Chuck Force Gauges



Measure chuck jaw clamping force at high speeds. Also available for other chuck measuring applications.

Drawbar Force Gauges



Measure tool clamping force to protect spindles and ensure machining accuracy.

Custom Machine Tool Gauges

Any gauge for any machine or machine tool.

