

The tool changer alignment tool is used to check automatic tool changer positioning between the gripper arm, magazine, and the spindle. Improper alignment can result in abnormal wear on the spindle interface, mis-clamping, dropped tools, etc. The tool checks axial alignment using pin (1) and radial alignment using pin (2).

The tool checks axial alignment using pin (1) and radial alignment using pin (2).


Taper	Order Number
Capto C3	440.110.C03.000
Capto C4	440.110.C04.000
Capto C5	440.110.C05.000
Capto C6	440.110.C06.000
Capto C8	440.110.C08.000
Capto C8X	440.110.C08X.000
Capto C10	440.110.C10.000

Also available for HSK and Steep Taper.

Preventive Maintenance Gauges

Dimensional Gauges, Balancing Masters, Coolant Supply Gauges, Center Height/Master Setting, Tool Changer Alignment Gauges, Machine Set-up Gauges. Also ask us about custom gauges and personalized solutions for your machine or machine tool.

Runout Test Arbors



Available for all major machine tapers, including CAT/DIN/BT Steep Taper, HSK, Capto, KM, Morse, and others.

Chuck Force Gauges



Measure chuck jaw clamping force at high speeds. Also available for other chuck measuring applications.

Drawbar Force Gauges



Measure tool clamping force to protect spindles and ensure machining accuracy.

Custom Machine Tool Gauges

Any gauge for any machine or machine tool.

