

- For tools with straight shank DIN 1835-A
- Pre-balanced per ISO 1940-1 up to 10,000 rpm
- Maximum runout between outer taper and collet housing is 0.003 mm
- Coolant tube to be ordered separately

All dimensions in mm.

D-HSK	Size	D ₁	L	D ₂	G	kg/lb	Order Number
40	ER25	1-16	80	42	M-10	0.80/1.76	612.140.025.080
40	ER32	2-20	100	50	M-16	1.00/2.20	612.140.032.100
50	ER25	1-16	80	42	M-10	0.90/1.98	612.150.025.080
50	ER32	2-20	100	50	M-16	1.20/2.65	612.150.032.100
63	ER25	1-16	80	42	M-10	1.10/2.43	612.163.025.080
63	ER32	2-20	100	50	M-16	1.40/3.09	612.163.032.100
63	ER40	3-26	120	63	M-16	1.50/3.31	612.163.040.120
80	ER32	2-20	100	50	M-16	2.80/6.17	612.180.032.100
80	ER40	3-26	120	63	M-16	3.00/6.61	612.180.040.120
100	ER32	2-20	100	50	M-16	3.00/6.61	612.190.032.100
100	ER40	3-26	120	63	M-16	3.10/6.83	612.190.040.120


OPTIONAL



Balanced Locknut



Bearing Locknut



Wrench

Collet	Balanced Locknut	Bearing Locknut	Wrench
ER25	049901 03 05	049901 04 05	049904 03 05
ER32	049901 03 06	049901 04 06	049904 03 06
ER40	049901 03 07	049901 04 07	049904 03 07

Other sizes and custom types are available - please contact us for more information.