



- Coolant tubes are for use with HSK-A, HSK-E, and HSK-F.
- Design meets dimensions of DIN 69893 and ISO 12164-1 and is fully replaceable with other coolant tubes.
- Coolant tubes are flexible and can easily move into the proper position for smooth contact. For example, for HSK-A 63 tubes, only 17 N force is required to deflect the tube one degree.
- Coating reduces friction and seal wear.

Taper	L	G	d	d1	L1	Order Number
HSK-A32	26	M10x1	6	3.5	5.5	699.100.132
HSK-A40	29.5	M12x1	8	5	7.5	699.100.140
HSK-A50	33	M16x1	10	6.4	9.5	699.100.150
HSK-A63	36.5	M18x1	12	8	11.5	699.100.163
HSK-A80	40	M20x1.5	14	10	13.5	699.100.180
HSK-A100	44	M24x1.5	16	12	15.5	699.100.190
HSK-A125		M30x1.5				699.100.192
HSK-A160		M35x1.5				699.100.196

Available for HSK-A 32, 40, 50, 63, 80, 100, 125, 160

TAC Rockford Product Line

Machine Tool Gauges, Tool Changer Alignment, Runout Test Arbors, Workholding Systems, Tool Holders, Adapters and Extensions, Tool Holder Blanks, Machine Tool Accessories, Coolant Tubes and Gauges, Heat Shrink Systems, Rapid Prototyping

Tool Holders



Gauges



Accessories



Rapid Prototyping

