



HSK-A	d1	A	Ref.no.	d2	d3	l1	g	L	V	kg
63	3.0	80	285.0000.322	19	22	-	-	112	-	0.7
63	4.0	80	285.0002.322	19	22	-	-	112	-	0.7
63	5.0	80	285.0003.322	19	22	-	-	112	-	0.7
63	6.0	80	285.0004.322	19	22	35	M 6	112	5	0.7
63	6.0	100	285.0034.322	19	22	35	M 6	132	5	0.7
63	7.0	80	285.0005.322	19	22	35	M 6	112	5	0.7
63	7.0	100	285.0035.322	19	22	35	M 6	132	5	0.8
63	8.0	80	285.0006.322	19	22	35	M 6	112	5	0.7
63	8.0	100	285.0036.322	19	22	35	M 6	132	5	0.8
63	9.0	80	285.0007.322	19	22	37	M 6	112	5	0.7
63	9.0	100	285.0037.322	19	22	37	M 6	132	5	0.8
63	10.0	80	285.0008.322	19	22	37	M 6	112	5	0.7
63	10.0	100	285.0038.322	22	22	37	M 6	132	5	0.8
63	11.0	100	285.0009.322	22	22	37	M 6	132	5	0.8
63	12.0	100	285.0020.322	27	30	37	M 6	132	5	0.8
63	16.0	100	285.0012.322	27	30	40	M 6	132	5	0.9

For coolant tubes see accessories page 4.8

For adjusting screws see accessories page 4.8

For shrink rings see accessories page 4.2

Design

The clamping diameter is designed for a shank tolerance of h9.

Note

Other designs and sizes are available on request.

Standard Specification

Shrink ring and adjusting screw for length adjustment (from Ø 6) are included.